

## **Typical Application: Medium Duty Trucks, 14,000 - 27,000 GVWR**

- Brush Finished Stainless Steel Moldboard
- Heavy Duty 48" X 4" Square Sector With Six 1/2" Trip Ears
- Massive, Robotically Welded 3/8" Plate Sector Construction
- Tall Moldboard With Aggressive Curvature & Overhang For Excellent Throwing Action
- Super-Duty 12" Belted Deflector
- Foot Pedal Operated Mounting For Easy Removal And Connection
- Super Bright Plow Lights With Vibration Resistant Double Stud Mounts.
- 5/8" Heavy Duty Cutting Edge
- Cast Iron Heavy Duty Shoes
- Fluorescent Orange Blade Guide Kit
- Integral Hydraulics Or Central Hydraulic Option

## DETAILED SNOWDOGG SNOWPLOW SPECS

MODEL	WIDTH	BLADE HEIGHT	MATERIAL	THICKNESS	ANGLE	LIFT	KINGPIN	WIDTH AT ANGLE	RIBS	SPRINGS	TRIP	CUTTING	WEIGHT	DEFLECTOR	SHOES
CM100	120"	31"	SS	.105"	2" x 12"	2" x 6"	1-1/8"	104"	9 <sup>2</sup>	6	Full	5/8" x 6"	1100 lbs. <sup>3</sup>	Std.	Cast

WEIGHT NOT INCLUDING TRUCK MOUNT, 40-80LBS. TYPICAL WEIGHT; <sup>2</sup>2 ARE DIAGONAL; <sup>3</sup>NOT INCLUDING SHOES

