
#### **HYDRAULICS**

#### HYDRASTAR™ HYDRAULIC PUMPS



#### A. - D. HydraStar™ Direct & Remote Mount Hydraulic Pumps w/Manual Valves

- · Cast iron roller bearing dump pump
- Designed for 2 or 3 line installations
- Rebuildable & comes with mounting bracket
- Direct mount pump includes a 4 bolt SAE B mounting flange and %"
   13 spline input shaft
- All C1010 Series pumps are 2½" dia. gear

For direct pumps, rotation must be specified.

# E. - F. HydraStar™ Direct & Remote Mount Hydraulic Pumps w/Manual Valves

- Ideal for small dump applications
- Mounting:
   CH101 (remote mount) 2 bolt
   mounting pad
   CH102 (direct mount) SAE B 4 bolt
  flange
- Porting:
   11/4" inlet, 3/4" NPT cylinder port,
   3/4" NPT return port

# G. - H. Air Shift Cylinder for Hydraulic Pumps w/ Manual Valves

- Converts manual pump operation to pneumatically controlled pump
- Complete with pump activator cylinder and mounting hardware

# I. Pump Support Bracket Kit

- Supports Buyers BPC1010-Series, HydraStar™ C1010
   Series, Commercial C101/ C102, Permco DM640-Series
- Kit Includes: Transmission Plate,
   (2) Pump Plates,
   (2) Coupling Nuts,
   (2) %" Bolts,
   (4) Flat Washers,
   (2) Lock Washers,
   Instructions

	PART NO.	DESCRIPTION	WEIGHT	CAT.
Α	C1010	Manual Valve Hydraulic Pump/Valve, Remote Mount, 1" Round		
		Shaft 1/4" x 11/4" Keyway	74.00 lbs.	620 (Y)
В	C1010AS	BPC1010 Hydraulic Pump, w/ AS301 Included, Remote Mount	76.00 lbs.	130 (Y)
C	C1010DMCW	For Clockwise Rotation, Direct Mount	74.00 lbs.	620 (Y)
C	C1010DMCCW	For Counterclockwise Rotation, Direct Mount	74.00 lbs.	620 (Y)
D	C1010DMCWAS	C1010DMCW Hydraulic Pump, w/ AS301 Included, Direct Mount	76.00 lbs.	130 (Y)
D	C1010DMCCWAS	C1010DMCCW Hydraulic Pump, w/ AS301 Included, Direct Mount	76.00 lbs.	130 (Y)
G	AS301 0*	Air Shift Cylinder	2.34 lbs.	646 (N)
G	AS302*	Air Shift Cylinder with Tubing & Fittings	2.65 lbs.	646 (N)
Н	BASK16 @*	Air Shift Cylinder	1.43 lbs.	646 (N)
Н	BASK16P <b>⊕</b> *	Air Shift Cylinder	1.38 lbs.	646 (N)

ORDERING INFORMATION									
	PART NO.	GEAR SIZE	MOUNTING	C.I.R.	FLOW @ 1000 RPM	FLOW @ 1800 RPM	MAX PRESSURE	WEIGHT	CAT.
Ε	CH101115	1½"	Remote	2.96	11.7	21	2500	35 lbs.	620 (Y)
Ε	CH101120	2"	Remote	3.94	16.1	29	2500	38 lbs.	620 (Y)
F	CH102115CCW	11/2"	Direct	2.96	11.7	21	2500	35 lbs.	620 (Y)
F	CH102115CW	1½"	Direct	2.96	11.7	21	2500	35 lbs.	620 (Y)
F	CH102120CCW	2"	Direct	3.94	16.1	29	2500	38 lbs.	620 (Y)
F	CH102120CW	2"	Direct	3.94	16.1	29	2500	38 lbs.	620 (Y)
Buyers offers replacement pumps (single, tandem, or piggyback) for: Commercial, Permco, Tyrone, Vickers & others									

RPM	GPM OUTPU			
600	13			
900	21			
1200	33			
1500	37.5			
1800	46			
• For u	se with:			
	arcial C101/C			

**BPC1010 Series** 

- O For use with:

  Commercial C101/C102

  Buyers BPC1010,

  BPC1010DM

  HydraStar™ C1010,

  Muncie E Series

  Permco DMD25/DM640

  Tyrone T101/T102
- ② For use with: Commercial G101/G102 HydraStar™ CH101/CH102
- S For use with:

  Buyers H101/H102

  Permco DM300/DM400

#### PUMP ROTATION

To identify pump rotation, view pump with shaft facing you and belly of pump down

ACCESSORIES							
	PART NO.	DESCRIPTION	WEIGHT	CAT.			
1	PB10	Pump Support Bracket Kit	2.8 lbs.	648 (N)			